

BEM600VGL Medium Grade Gridlock Vinyl Panel


PSA MOB PF2 PS/SPU Medium Grade

The panel consists of a high grade, FSC® certified, 30mm high density particle board core in a sandwich construction with steel top and bottom sheet that has the Gridlock Frame assembled onto bottom of the Panel. It is then covered with our standard static dissipative Gerflor Mipolam EL7 Permaflor Dark Grey Vinyl or other customer approved. This then has a Full depth ABS edge band applied creating a fully encapsulated 600mm² panel to be laid with complete electrical continuity and has a high resistance to damage. The Panel fits existing Gridlock Systems with the Castle Headed Pedestal.

Product	Panel Grade	Point Load (25mm x 25mm)	Load Over (300mm x 300mm)	Uniform Distributed Load	Panel Thickness (Nominal)	System Weight (Typical)
BEM600VGL	Medium	3.0 kN	4.5 kN/m ²	8.0 kN/m ²	33mm + Frame	40kg/m ²

Certification

The panel meets the loadings of the PSA MOB PF2 PS/ SPU March 1992 Medium Grade specification. All of the Permaflor PSA panels have a 3 times working load safety factor, Class "O" spread of flame resistance and a 25 year warranty. Full FSC accreditation No FSC-ACC-008 TT-COC-003493.



Galvanised steel top and bottom Sheet with Gridlock Frame assembled to bottom of panel.



Full depth ABS Edging

Finish

All Permaflor Heavy Grade edge banded conglomerate panel can have a wide range of factory bonded conglomerate tile finishes including Porcelain, Marble, reconstituted Stone, ideal for reception and high profile area's. Whatever your requirement, Permaflor will have the flooring solution to suit you.

Manufacture

All panels are manufactured in our facility in the UK, which allows us to offer total flexibility whilst maintaining the highest possible quality standard and ensures fast reaction and a reliable service. Materials used are sourced from high quality suppliers and use renewable, sustainable sources and suppliers wherever possible. We can also offer a bespoke service and specialise in replicating and reproducing existing raised floors.



Permaflor
access flooring solutions

The first choice for access flooring systems

For more information call
01432 347 722
sales@permaflor.co.uk